

INVITATION TO TENDER



Implemented by:
giz Deutsche Gesellschaft
für Internationale
Zusammenarbeit (GIZ) GmbH

SUPPLY OF GENERAL ITEMS AND AGRIC INPUTS

Deutsche Gesellschaft für Internationale Zusammenarbeit (GIZ) intends to tender for the Supply of General Items and Agric Inputs in Lots.

The GIZ Office Accra invites tenderers to submit, free of charge and without obligation on the part of GIZ, a tender based on the following terms and conditions. Non-conformity with all conditions mentioned could lead to the exclusion of the bid.

A) Conditions of the bid

- Tenders should be valid for a period of **three (3) months** after the deadline of Tender submission.
- Prices shall be fixed prices. Prices shall be free of VAT and other public charges. Prices shall be quoted in Ghana Cedis.**
- All interested suppliers are required to submit a letter, a company profile, and their quotes according to the specifications below:

B) Specifications

| No. | Item | Specifications | Qty | Unit of Measure |
|-------------------------------------|---------------------------------|---|-----|-----------------|
| LOT 1 SUPPLY OF HEADSETS | | | | |
| 1 | Type 2: Wired Headset | Type 2 – Wired Headset <ul style="list-style-type: none"> Connectivity: Wired (USB-A/USB-C) or Wireless (Bluetooth 5.0 or USB dongle) Microphone: Boom mic with passive noise cancellation Sound: Enhanced stereo or basic surround sound, 20Hz–20kHz Comfort: Padded ear cups (faux leather or fabric), adjustable padded headband Controls: On-ear controls or inline controls (volume, mute, call pick-up) Durability: Reinforced frame | 18 | Pieces |
| 2 | Type 3: Wired Headset | Type 3: Wired Headset <ul style="list-style-type: none"> Connectivity: Dual (USB-C/Bluetooth multipoint, optional 3.5mm) Microphone: AI-powered or active noise-cancelling boom mic Sound: High-fidelity audio, wide frequency response (e.g., 10Hz–30kHz), surround sound (7.1 or spatial audio) Comfort: Memory foam ear cushions, lightweight build, ergonomic design Controls: Touch controls or advanced on-ear buttons (customizable) Durability: Premium build (metal/plastic composite), replaceable parts Extras: ANC (Active Noise Cancelling), app customization, long battery life (20–40+ hours) | 7 | Pieces |
| 3 | Type 4: Wireless Headset | Type 4: Wireless Headset <ul style="list-style-type: none"> Connectivity: Bluetooth 5.0 or higher, Multipoint Connectivity: Yes; Wireless Range: between 10m - 30m Active Noise Cancellation (ANC): Adaptive and Hybrid: Yes Microphone & Call Quality: Number of Mics: 2 - 6 Mics, Environmental Noise Cancellation(ENC): Yes Battery Life & Charging: Playtime: 20 - 50 hours on a single charge, Fast Charging MS Teams Support Replaceable Earcups | 45 | Pieces |
| LOT 2 SUPPLY OF PPEs | | | | |
| 4 | Hand Gloves | Hand gloves (non-powdered latex examination gloves) <ul style="list-style-type: none"> Type: Material: Nitrile, Stretchable, Non-Powdered 100 pieces per pack Size: one size fits all Colour: Blue | 75 | Packs |
| 5 | Hand Gloves | Hand Gloves (Black rubber gloves) <ul style="list-style-type: none"> Suitable thickness. 50 pairs per box Colour: black, green or orange Made of Natural rubber Stain concealment Reusable Not easy to crack, Chemical resistant gloves that protect hands from harsh detergents, chemicals, hot water, household cleaners, a broad range of solvents, animal fats, etc. Lightweight and durable. | 35 | Boxes |
| 6 | Safety boots-Type 1 | Safety boots-Type 1 <ul style="list-style-type: none"> Water resistant Brown leather Durable leather upper Steel toe cap Dual density Pu-sole Easy to wear and convience Sizes: 42, 43, and 44 (5-pairs of each size) | 15 | Pairs |

| | | | | |
|----|----------------------------|--|-----|--------|
| 7 | Safety boots-Type 2 | Safety boots-Type 2 <ul style="list-style-type: none"> Anti slip and water resistant Bufalo black leather Durable leather upper Steel toe cap Dual density Pu-sole Easy to wear and convience For construction and manufacturing. Sizes: 42, 43, and 44 (5-pairs of each size) | 15 | Pairs |
| 8 | Reflective Overalls | Reflective Overalls <ul style="list-style-type: none"> Overalls Cotton 2 front pockets with Flap and snap fastening. 2 cross side pockets 2 back straight cut patch pocket with Velcro/ Snap as closure Pen pocket on left sleeve – for fast access to a pen when needed. Two-way FR zipper closure to the centre front Elasticated waist – ensures improved comfort and better garment fit. Double needle stitching on Pocket, Cuff and Arms 2" wide FR reflective strips over shoulders, arms, waist and legs – for added High visibility and safety Color – Blue black or Green Sizes (small, medium, large, extra-large) 50 pieces of each size | 200 | Pieces |
| 9 | Factory Scrubs | Factory Scrubs <ul style="list-style-type: none"> Type: Made of cotton Colour: Sea blue Durable fabrics Antimicrobial properties Can withstand heavy use and cleaning | 100 | Pieces |
| 10 | Half face mask | Half face mask (respirator) with filter cartridge <ul style="list-style-type: none"> Reusable Allows for replaceable filter cartridge Medium size Easy to adjust head straps Soft and lightweight Compatible with organic vapour cartridges | 175 | Pieces |
| 11 | Goggles | Goggles <ul style="list-style-type: none"> Eye protection Adjustable band Anti-dust Anti-splash Anti-fog Uv protective Air Space Virgin polycarbonate optical grade | 400 | Pieces |
| 12 | Wellington Boots | Wellington Boots <ul style="list-style-type: none"> Colour: Black Waterproof Durable and grippy sole Comfortable fit Natural rubber Cleanability Size: 41 pieces (15 pairs) Size: 42 (70 pairs) Size: 43 (160 pairs) Size: 44 (160 pairs) Size: 45 (30 pairs) Size: 46 (5 pairs) | 440 | Pairs |
| 13 | Disposal hair net | Disposal hair net <ul style="list-style-type: none"> Type: Disposable, Non-Woven Elastic Stripe Size: Regular (12 inch) Colour: Green or Blue Color: white or blue 1000pieces/carton or 100pc/box Material: Rubber Length: Below knee-high Waterproof Necessary safety or hygiene on Closure: Slip on | 300 | Packs |
| 14 | Disposal shoe cover | Disposal shoe cover <ul style="list-style-type: none"> Colour: Blue or green Water resistant Packed 100 pieces per box Anti-slip design | 200 | Boxes |
| 15 | Disposal nose mask | Disposal nose mask <ul style="list-style-type: none"> Type: 3Layer Plated Nose Mask Measurement: Rectangular (10cm x 19cm) Colour: Sea Blue Sample: sku no.: SF1033560084-220" Pack 50 pieces per pack | 200 | Packs |
| 16 | Transportation | Abura Asebu & Tumu – Sissala East District | 1 | |

continue to next page

...CONTINUED FROM PREVIOUS PAGE

INVITATION TO TENDER

SUPPLY OF GENERAL ITEMS AND AGRIC INPUTS



| LOT 3 SUPPLY OF EQUIPMENT & ACCESSORIES | | | | | |
|--|---|--|-----|---------|---|
| 17 | Mist Blower | Mist Blower <ul style="list-style-type: none">Type: Petrol Engine Mist BlowerDisplacement 72.3cc2 stroke petrol enginesSpray nozzle for long reach with high air exit velocityPower Output: 3.0kW / 4.1HPHorizontal reach: 13-meterDry Weight: 11.0kgFuel tank: 1.4 LitersFor the application of organic fungicides and organic liquid fertilizersMade in Germany | 13 | Pieces | |
| 18 | Knapsack Sprayer | Knapsack Sprayer | 10 | Pieces | |
| | | <ul style="list-style-type: none">Hose | | | <ul style="list-style-type: none">1.3m (PVC) |
| | | <ul style="list-style-type: none">Standard nozzle | | | <ul style="list-style-type: none">Metallic adjustable conical |
| | | <ul style="list-style-type: none">Lance | | | <ul style="list-style-type: none">Chromed-plated brass lance |
| | | <ul style="list-style-type: none">Useful capacity | | | <ul style="list-style-type: none">16L |
| | | <ul style="list-style-type: none">Total capacity | | | <ul style="list-style-type: none">16.7L |
| | | <ul style="list-style-type: none">Litres/Min. 1.5bar | | | <ul style="list-style-type: none">0.7l/min |
| | | <ul style="list-style-type: none">Litres/Min. 3bar | | | <ul style="list-style-type: none">1l/min |
| | | <ul style="list-style-type: none">Net weight | | | <ul style="list-style-type: none">3.40kg |
| | | <ul style="list-style-type: none">Wide filler opening | | | <ul style="list-style-type: none">Yes |
| | | <ul style="list-style-type: none">Set of nozzles for herbicide and insecticide treatment | | | <ul style="list-style-type: none">Yes |
| | | <ul style="list-style-type: none">Standard accessories | | | <ul style="list-style-type: none">Pressure regulator, set of nozzles (herbicide elbow plus fan, mirror and disc nozzles), two seals (1 rubber and 1 synthetic) and a dispenser. |
| | | <ul style="list-style-type: none">Lance and extension | | | <ul style="list-style-type: none">Lance and Lever |
| | | <ul style="list-style-type: none">Straps | | | <ul style="list-style-type: none">adjustable and padded |
| <ul style="list-style-type: none">Chamber seal | <ul style="list-style-type: none">Synthetic | | | | |
| <ul style="list-style-type: none">Pressure regulator | <ul style="list-style-type: none">Yes (3 positions) | | | | |
| <ul style="list-style-type: none">Handle | <ul style="list-style-type: none">PP | | | | |
| 19 | Brush Cutter | Brush Cutter <ul style="list-style-type: none">4 stroke engineEngine Displacement: 75 ccTo support weeding of organic citrus farms | 12 | Pieces | |
| 20 | Motorized pruner | Motorized pruner <ul style="list-style-type: none">25.4 cc professional-grade, 2-stroke engineCollapsed length 107 inchesExtended length 146 inchesLoop style handle | 5 | Pieces | |
| 21 | Brush cutter blade | Brush cutter blade | 5 | Pieces | |
| 22 | Brush cutter blade head | Brush cutter blade head | 3 | Cartons | |
| 23 | Brush Cutter | Brush Cutter <ul style="list-style-type: none">ClutchStrong and Durable | 5 | Pieces | |
| 24 | Brush Cutter | Brush Cutter <ul style="list-style-type: none">Timing BeltStrong and durable | 5 | Pieces | |
| 25 | Mist blower starter | Mist blower starter | 5 | Pieces | |
| 26 | Mist blower spark plug | Mist blower spark plug | 100 | Pieces | |
| 27 | Mist blower Carburetor | Mist blower Carburetor | 5 | Pieces | |

| 28 | Motorized pruner cutter chain | Motorized pruner cutter chain | 5 | Pieces |
|--|-------------------------------|--|---|--------|
| 29 | Transportation | Abura Asebu | 1 | |
| LOT 4 SUPPLY OF TOOLS AND EQUIPMENT | | | | |
| 30 | Metal Detector | Metal Detector <ol style="list-style-type: none"> Frequency Operation <ul style="list-style-type: none"> Single Frequency Selection: User-selectable options of 100, 300, or 600 kHz for high-tuned detection. Optimized Coil Geometry: Enhances sensitivity and detection accuracy. Detection Sensitivity <ul style="list-style-type: none"> Patented Technology: Improves sensitivity to detect metallic contaminants. Detection Range: 500-1000 mm, 250-550 mm (for compact setups) User Interface <ul style="list-style-type: none"> 7" WVGA Touchscreen: Intuitive control panel supporting both metric and imperial units. Auto Setup and Maintenance <ul style="list-style-type: none"> PMR Wizard: Guides setup and maintenance scheduling. PMR Alarm: Alerts users to due tests and logs pass/fail results. Connectivity and Data Management <ul style="list-style-type: none"> USB port and ProDX-enabled for reporting, software upgrades, and diagnostics. OPC UA and PackML integration for industry-standard communication. Durability and Build Quality <ul style="list-style-type: none"> Protection Ratings: IP65 - Light-duty, IP66 - Medium-duty, IP69K - Heavy-duty (washdown conditions) Material: SS304 or SS316 stainless steel with bead-blast or brushed finish. Operating Temperature: -10°C to +45°C Power Supply <ul style="list-style-type: none"> Input Voltage: 100 - 240 VAC Max Power Consumption: 220W Logging and Alarms <ul style="list-style-type: none"> System Logs: Tracks Access, Alarms, Detections, and PMR activities. Other Features <ul style="list-style-type: none"> Visual Indicators: Color-coded bar graphs for pack count and reject count. Includes in-feed sensors and configurable warning alerts. Provides enhanced reject monitoring features. | 1 | Pieces |
| 31 | Multi-layer industrial sieve | Multi-layer industrial sieve <ol style="list-style-type: none"> Sieving Configuration <ul style="list-style-type: none"> Layers: 4-layer screen setup for multi-grade material separation Discharge Ports: 5 outlets for sorting materials into various sizes or grades Particle Size Range <ul style="list-style-type: none"> Processing Capacity: Suitable for particles from 50 microns to 20 mm Applications: Ideal for industries such as food processing, pharmaceuticals, and chemicals Material Construction <ul style="list-style-type: none"> Contact Parts: SS316L or SS304 stainless steel Operation & Controls <ul style="list-style-type: none"> Control Interface: Simple button control system for user-friendly operation Material Handling: <ul style="list-style-type: none"> Feeding: Manual loading Discharge: Gravity-based discharge for energy efficiency Mobility <ul style="list-style-type: none"> Mounting: Equipped with movable wheels with brakes Functionality: Easy to relocate and securely lock in place during operation Electrical Requirements <ul style="list-style-type: none"> Power Supply: Standard: 3-phase, 380V, 50Hz | 1 | Pieces |

continue to next page

...CONTINUED FROM PREVIOUS PAGE

INVITATION TO TENDER

SUPPLY OF GENERAL ITEMS AND AGRIC INPUTS



| | | | | |
|----|------------------------------|--|---|--------|
| 32 | Commercial Dehydrator | Commercial Dehydrator <ol style="list-style-type: none"> Drying Capacity <ul style="list-style-type: none"> Rack Configuration: 96 stainless steel trays Application: Suitable for large-scale dehydration of fruits, vegetables, meats, and other food items Design: Optimized for high-volume commercial use Airflow and Fan <ul style="list-style-type: none"> Fan System: 8 x 6.5-inch high-power fans Air Distribution: Ensures uniform airflow across all trays for consistent drying performance Power and Electrical <ul style="list-style-type: none"> Voltage: 208-240V Power Consumption: 4800W Amperage Draw: 30 Amps Control System <ul style="list-style-type: none"> Interface: Digital touchscreen Timer: Programmable up to 99 hours Temperature Range: 70°F to 180°F (21.1°C to 82.2°C) Zonal Programming: Independent time and temperature control for each of the two drying zones Dual-Zone Control <ul style="list-style-type: none"> Zones: Two independently controlled zones Functionality: Enables simultaneous drying of different food types at varied temperatures and durations Automatic Safety & Energy Features <ul style="list-style-type: none"> Auto Cool Down: Prevents overheating and enhances energy efficiency Auto Shut-Off: Ensures safety and reduces energy consumption Construction & Certification <ul style="list-style-type: none"> Material: Full stainless steel body and interior Durability: Corrosion-resistant, easy to clean, and built for commercial kitchen environments Certification: NSF approved for food safety and hygiene compliance | 1 | Pieces |
| 33 | Motorized Tricycle | Motorized Tricycle <ul style="list-style-type: none"> Engine Capacity 210cc Displacement 250cc, Single Cylinder, Air-Cooled Fuel Type Petrol Cooling System Water-Cooled with Fan Starting Method Kick and Electric Start Brake System Mechanical Tread 1,110 mm Fuel Consumption 5L / 100 km Loading Capacity 2,000 kg or higher Rear Axle Type Full Floating Helping Gear Yes DVLA Registration Yes | 1 | Pieces |
| 34 | Rice Harvester | Rice Harvester <ul style="list-style-type: none"> Type Walk-behind Power Reaper Harvesting Rows 2 Rows Application Harvesting paddy/rice, wheat, barley, and similar crops Engine Power 5.5 - 7.5 HP (Petrol or Diesel) Fuel Type Petrol or Diesel Cutting Width Approx. 800 - 1000 mm Working Capacity 0.3 - 0.5 hectares per hour Harvesting Height Adjustable (typically 30-60 cm) Transmission Gear-driven or belt-driven Start Type Recoil (manual) or Electric Start Drive Type Self-propelled Cutting Blade Type Serrated reciprocating blades Wheel Type Pneumatic or rubber lug wheels Straw Management Windrowing or side discharge Portability Foldable handle and transport wheels for easy movement Crop Residue: Low stubble height, minimal grain loss | 1 | Pieces |
| 35 | Engine | <ul style="list-style-type: none"> Engine Engine Type: Radiator-cooled, 4-stroke diesel engine Horsepower (HP) 18 HP Cooling System Radiator (water-cooled) Fuel Type : Diesel Starting Method : Manual or Electric Start Engine Speed Approx. 2200 - 2400 RPM Fuel Tank Capacity 5 - 10 liters Lubrication System Forced lubrication Usage Suitable for tricycles, pumps, tillers, small machinery Engine Displacement Approx. 900 - 1000 cc Accessories : Radiator, fan, fuel tank, exhaust, tool kit | 1 | Pieces |

| | | | | |
|---|---|--|---|--------|
| 36 | Grain moisture meter | Grain moisture meter <ul style="list-style-type: none"> Fort pin type Application Moisture measurement in grains Measurement Method Electrical resistance via pin probes Measurement Range Typically 5% - 40% (varies by model) Display Digital LCD display Power Supply Battery operated Portability Handheld and lightweight Usage Suitable for use in field or lab Grain Types Supported Maize, rice, wheat, sorghum, millet, and others Calibration Manual/automatic calibration Durability Rugged design for field conditions Accessories Comes with carry case and user manual | 1 | Pieces |
| 37 | Digital Weighing Scale | Digital Weighing Scale <ol style="list-style-type: none"> Capacity & Type <ul style="list-style-type: none"> Maximum Weight Capacity: 300 kg Scale Type: Digital electronic weighing scale for precise measurements Mobility <ul style="list-style-type: none"> Wheels: Integrated wheels for easy movement and repositioning within facilities Construction <ul style="list-style-type: none"> Build Quality: Constructed from durable materials to withstand heavy-duty, industrial use Design: Robust frame suitable for commercial and industrial environments | 1 | Pieces |
| 38 | Wheel barrow | Wheelbarrow 150 Kg capacity | 1 | Pieces |
| 39 | Packaging sealing sewing Machine | <ul style="list-style-type: none"> Packaging sealing sewing Machine Rechargeable type Type Handheld, Rechargeable Packaging Sealing Sewing Machine Application Sealing and stitching of packaging materials (e.g., sacks, bags, woven fabric) Power Supply Rechargeable Lithium Battery Battery Runtime Approx. 2-4 hours (depending on usage) Charging Time 2-3 hours Motor Type High-speed electric motor Stitch Type Single-thread or multiple chain stitch Sealing Speed Approx. 8-10 meters per minute Material Compatibility Suitable for jute, polypropylene (PP), paper bags, woven sacks, etc. Body Material Durable ABS/plastic or aluminium alloy housing Weight Lightweight, portable (approx. 1.5-2.5 kg) Accessories Charger, needles, thread spools, toolkit Operation Manual trigger with automatic thread cutter Noise Level Low to moderate Safety Features Overcharge protection, ergonomic handle | 1 | Pieces |
| 40 | Transportation | Kumasi | 1 | |
| LOT 5 IT AND OTHER EQUIPMENT | | | | |
| 41 | Laptop | Laptop <ul style="list-style-type: none"> Processor: Intel® Core™ i7 1355U, 13th Generation. Memory (RAM): 8GB Storage: 512GB SSD Display: 15.6" | 2 | Pieces |
| 42 | Mobile Phones | Mobile Phones <ul style="list-style-type: none"> Operating System: Android 14, One UI 6 Memory: 256GB 8GB RAM Display: 6.5 inches, 103.7 cm² Resolution: 1080 x 2340 pixels Battery: 5000 mAh | 3 | Pieces |
| 43 | Tablet | Tablet <ul style="list-style-type: none"> 8 GB RAM + 128 GB, Display: 8.7" WXGA+LCD (800 x 1340), Processor: Octa-Core Mediatek Helio G99, RAM: 8GB, Storage 128 GB expandable up to 1TB via microSD, Operating system: Android 13 with One UI 5.1, Audio: Dual Speakers with Dolby Atmos, Battery: 5100mAh, Camera: 8MP Rear / 2MP Front, Connectivity: Wi-Fi, Bluetooth 5.3, USB-C | 2 | Pieces |

continue to page 19

...CONTINUED FROM PAGE 17

INVITATION TO TENDER

SUPPLY OF GENERAL ITEMS AND AGRIC INPUTS



| | | | | |
|---|---------------------|---|-----|--------|
| 44 | Motorcycle | <ul style="list-style-type: none"> Motorcycle Engine Capacity: 193.27cc Fuel Type: Petrol Number of wheels: 2 Dimension: 2080*800*1190 Front tyre: 90/90 - 19 Rear tyre: 110/90 - 17 Wheelbase: 1330mm Ground Clearance: 255mm Seat height: 845mm Curb Weight: 130kg Front Rims: Mesh wheel - 1.85*19 Rear Rims: Mesh wheel - 2.15*17 Tread: Loading Capacity/Load: 150kg Max Speed: 103km/h Bore*Stroke: 63*62mm Compression Ratio: 9.0:1 Igniter: C.D.I Transmission: Chain Max Power: 9.8kw/7500rpm Max Torque: 14.0N.m/7500rpm Cooling System: Air-cooled Displacement: Single cylinder/ 4 stroke/ air-cooled Fuel Consumption: Fuel Tank Capacity: 11L Brake Method: Front disc/Rear drum Starting method: Self/Kick Registration with DVLA: Yes Helmet: Yes | 2 | Pieces |
| 45 | Drying Tent | Drying Tent <ul style="list-style-type: none"> Area - 150 sqm Length - 15 m Breadth - 10 m Height - 5.1m Wind resistance - 120kph Trellis - Built-in Side vent - 1.5m Ventilation - Fix-vent Solar | 1 | Pieces |
| 46 | Mini Dryer | <ul style="list-style-type: none"> Mini Dryer 32 sq.ft size 8ft x 4 ft Construction Material GI Pipe Structure Covering Materials Multiwall polycarbonate sheet Temperature and Humidity Controlling 1 no Solar PV module 100 Wp Electrical Heater backup 1.5 kw Stainless-Steel Perforated Trays 8 no Stainless-Steel Plain trays Solar powered | 2 | Pieces |
| LOT 6 SUPPLY OF AGRIC INPUTS | | | | |
| 47 | Motorized Tricycles | Motorized Tricycles <ul style="list-style-type: none"> Engine capacity - 210cc Fuel Type- Petrol Number of wheels - 3 Dimension - 3580*1390*1415* Cargo Box - 2000*1300*300 Front Tyre - 5.00-12 Rear Tyre - 5.00-12 Wheelbase - 2330 Tread - 1110 Loading Capacity - 2000kg Max speed - 60km/h Cooling system - Single cylinder water cooled with fan Displacement - 250cc single cylinder air cooled engine Fuel consumption - 5L/100km Brake method - Mechanical Starting method - Kick and electric Rear Axes - Full Floating Helping Gear - Yes Registration with DVLA - Yes | 10 | Pieces |
| 48 | Pallets | Pallets <ul style="list-style-type: none"> Size - 4.5 feet * 2 inches * 4 feet Material - Wood | 200 | Pieces |

| | | | | |
|----|----------------|--|----------|--------|
| 49 | Cowpea | <ul style="list-style-type: none"> Cowpea 4,800 kg Quantity per acre: 8kg Plant Spacing: 60cm x 20cm. Seed shape: kidney shape. Seed color: large white seeds with a brown eye. Growth habit: erect growth habit. Maturity period: 60-70 days after sowing. Yield potential: yield potential of 6-7 bags (100kg) per acre. Pest and Disease Resistance: resistance to root rot disease, aphids, and tolerance to drought spells. Seed shelf life: For propagation purposes, the shelf life should not exceed one year. | 4,800 kg | KG |
| 50 | Transportation | Delivery to Tumu | 1 | Pieces |

C) Bid documents

Tenderers will be required to provide the following:

- Signed letter of bid with
 - priced quotation to the **required specification and conditions**
 - indication of **delivery period**
- Company profile, max. 5 pages A4
- Commercial qualification**
 - Valid Tax Clearance Certificate,
 - Business Registration Certificate,
 - VAT Registration Certificate,
 - Valid SSNIT Clearance Certificate
 - Declaration of Business Ownership by General Manager (Inclusion of Form A for Sole Proprietorship or Form 3 for Limited Liability)

PLEASE NOTE:

THE CURRENCY OF YOUR OFFER SHOULD BE IN GHANA CEDIS

ALL PROSPECTIVE BIDDERS ARE REQUIRED TO PERFORM THEIR TAX OBLIGATIONS IN GHANA.

Tenders should be submitted in LOTS

Tenders should be sealed and marked as:

LOT 1: 91188284 / 19.4933.8-001.99 "Supply Headsets"

LOT 2: 91188288 / 19.4933.8-005.00 "Supply of PPEs"

LOT 3: 91188292 / 19.4933.8-005.00 "Supply of Equipment & Accessories"

LOT 4: 91188293 / 19.4933.8-005.00 "Supply of Tools and Equipment."

LOT 5: 91188295 / 19.4933.8-007.00 "Supply of IT and other Equipment."

LOT 6: 91188297 / 19.4933.8-007.00 "Supply of Supply of Agric Inputs."

Tenders should be sent to the following address:

The Procurement Unit
GIZ Ghana
No. 7 Volta Street, Airport Residential Area, Accra
P.O. Box KA 9698,
Accra

To All Bidders:

- Bids must be submitted at the **GIZ Ghana Country Office Reception**.
- The deadline for submission is **24.06.2025 until 11:59 PM**.
- Documents should be submitted as early as possible before the deadline.
- Should the reception be closed, documents might exceptionally be dropped off at the guard's booth.
- The guards need to be told by the person submitting the documents that they are submitting tender documents.
- Always send a receipt with your documents stating the number of the tender.
- This receipt will be signed by the receptionist or a guard (in case of exceptional drop off at the guard's booth) to provide the bidder with proof of delivery / submission.

>Please note that participating in a tendering process of GIZ is free of charge for bidders.

At no phase of the process is the bidder required to make any payment to GIZ or to one of its employees.

Kindly Note by sending in your offer, you are agreeing to the GIZ General Terms and giving us the consent to process your company data.

ONLY SHORTLISTED FIRMS WILL BE CONTACTED